

AXIS TP3101 Pendant Wall Mount

Clean, simple design for fixed domes

AXIS TP3101 Pendant Wall Mount allows a clean, pendant-style mounting of AXIS P32-V/-LV cameras without the need for additional pendant kits. The concealed mounting makes it blend in with the wall. The compartment allows for secure storage of connectivity devices, microphone, and even AXIS I/O Indication LED. This compact mount is helpful to position the camera exactly where you need it, such as for installations above shop fronts with Axis retail analytics, such as people counting and face recognition.

- > **Contemporary design, becomes one with the wall**
- > **Concealed cabling and mounting screws**
- > **Compartment for microphone and connectivity devices**
- > **Mount on walls, counter tops, and ceilings**



AXIS TP3101 Pendant Wall Mount

General	
Supported products	AXIS M32 Series AXIS P32 Series
Casing	Cover: PC ABS blend Bottom bracket: Glass fibre reinforced polyamide Color: white NCS S 1002-B
Sustainability	PVC free, 22% recycled plastics
Dimensions	204 x 148 x 42 mm (8.0 x 5.8 x 1.7 in)
Weight	228 g (0.50 lb)
Maximum load	3 kg (6.6 lbs)
Environment	Indoor
Operating conditions	-10 °C to 50 °C (14 °F to 122 °F) Humidity 10–85% RH (non-condensing)
Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)
Included accessories	Installation Guide Camera mount screws
Optional accessories	AXIS TP3701 J-box and Pole Adapter AXIS T8643 PoE+ over Coax Compact AXIS T6101 Audio and I/O Interface AXIS Device Microphone A AXIS Device Microphone B for P-line cameras Axis I/O Indication LED
Warranty	3-year warranty, see axis.com/warranty

Environmental responsibility:

axis.com/environmental-responsibility