


## TECHNICAL DATA SHEET LOW VOLTAGE BUILDING WIRE

Cable Description:

 Cu / PVC 450 / 750 V H07V2-R 90 °C 2.5 mm<sup>2</sup> RM G / Y

Design and Construction Data:		
Reference Manufacturing Standards		IEC 60228, IEC 60227-3, BS EN 50525-2-31
Max. Permissible Continuous Conductor Temp	°C	90
Max. Conductor Short Circuit Temp for 5 Seconds	°C	160 °C
Rated Voltage	V	450 / 750
Conductor Size	mm <sup>2</sup>	2.5
Conductor Material & Shape		Copper & Stranded Class 2 non-compacted Round Shape
Insulation Material		PVC
Nominal Insulation Thickness	mm	0.80
Insulation Color		YELLOW WITH GREEN STRIPES
Approximate Wire Overall Diameter	mm	3.6
Electrical Data:		
Max Conductor DC resistance @ 20 °C	ohms/km	7.4100
Max Conductor AC resistance @ 90 °C (Two/Three) Conductors	ohms/km	9.4485 / 9.4485
Max Conductor Short Circuit Current @ 1 Second	KA	0.25
Current Carry Capacity @ 30 °C Ambient Temperature		
Enclosed in conduit <sup>(1)</sup>		
Two Insulated Conductors Single Phase ac or dc	A	28
Three or Four Insulated Conductors Three Phase ac	A	24
Clipped direct <sup>(2)</sup>		
Two Insulated Conductors Single Phase ac or dc	A	31
Three or Four Insulated Conductors Three Phase ac	A	29
(1) Current carrying capacity based on IEE wiring regulation method B cables single ac or dc / three phase ac, enclosed in conduit on a wall or in trunking etc. at 30 °C ambient temperature". (2) Current carrying capacity based on IEE wiring regulation method C cables single ac or dc / three phase , clipped direct at 30 °C ambient temperature". * ref (IEE Wiring Regulations 17th edition Table 4D1A)		
The Cable shall meet all Test requirements of: IEC/BS EN 60228, IEC 60227-3, BS EN 50525-2-31, IEC 60332-1		
Packing Data:		
Type		Coil
Length of Cable per Coil (± 2%)	m	92
Net Weight (Approximate)	kg	3.0
Cable Marking:		
BAHRA CABLES CO. KSA 2.5 MM <sup>2</sup> CU/PVC 90 DEG C 450 / 750 V H07V2-R BS EN 50525-2-31 SASO 1320 TYPE 60227 IEC 01 FR IEC 60332-1		
Cable Drawing		
		
Description	Cu / PVC 450 / 750 V H07V2-R 90 °C 2.5 mm <sup>2</sup> RM G / Y	Approx. Diameter
1	Copper conductor with round shape	1.98
2	PVC TI-3 Insulation	3.58