

Molveno Stones

Collection	Molveno
Style Name	Molveno Stones
Style Number	C0109
Product Type	LVT
Size	11.75 in X 35.75 in
Installation	Brick Ashlar

Feature	Description
Overall Thickness	6 mm
Wear Layer	20 mil (0.5 mm)
Finish	M-Force™
Surface Profile	Embossed In Register
Edge Profile	Micro-beveled Edge
Squareness	(ASTM F2421) Passes
Square Ft per Carton	17.5
Pounds per Carton	36.18
Pieces per Carton	6
Classification	ASTM F1700 - Class III, Type B - Embossed
Size and Tolerance	(ASTM F2055) Passes
Recommended Adhesive	None Required
Type of Construction	Commercial Grade Rigid Luxury Vinyl Tile
Thickness	(ASTM F386) Passes
Installation Method (Click or Glue)	Click




Recommended Installation Methods



Brick Ashlar



Brick Ashlar



Brick Ashlar

Colorways



Perfect Greige

Color code: 879
Style number: C0109



Software

Color code: 889
Style number: C0109



Grey Matters

Color code: 979
Style number: C0109



Cityscape

Color code: 988
Style number: C0109



Night Owl

Color code: 997
Style number: C0109

Performance

Feature	Description
Static Load	(ASTM F970) 1500 psi
Dimensional Stability	(ASTM F2199) Passes
Residual Indentation	(ASTM F1914) Passes
Resistance to Chemicals	ASTM F925 - Passes - No more than a slight change
Resistance to Heat	ASTM F1514 - Passes - ΔE < 8
Resistance to Light	ASTM F1515 - Passes - ΔE < 8
Critical Radiant Flux	ASTM E648 - Passes - ≤ 0.45 watts/cm ² , Class 1
Smoke Density	(ASTM E-662) ≤ 450
Thickness	(ASTM F386) Passes

Sustainability

Feature	Description
Floor Score	Floor Score Certified
Country of Origin	China
Mindful Materials	Participates in Mindful Materials Library
Environmental Product Declaration	EPD Vinyl Tile
Beyond Carbon Neutral	This product is 100% carbon neutral plus an additional 5% offset
Carbon Handprint	-0.095 kg CO ₂ e/ft ²
Embodied Carbon	1.9 kg CO ₂ e/ft ²

Warranties

Limited 15 Year M-Force Commercial Warranty