

Gradus & NBS Specifications

Esplanade 9000 Primary Barrier Matting

Data Sheet: Page 1 of 1 19.01.22

Gradus is a member of NBS Plus, providing a comprehensive library of pre-written specifications supported by guidance notes. The NBS specification for Esplanade 9000 is shown below, plus a detailed Gradus specification and profile description to ensure the correct specification is maintained. For further information on NBS contact NBS Services on 0191 232 9594.

NBS Specification

N10 GENERAL FIXTURES/FURNISHINGS/EQUIPMENT

300 ENTRANCE MATTING / 40 MISCELLANEOUS FITTINGS

Manufacturer: Gradus Accessories, Park Green, Macclesfield, Cheshire, SK11 7LZ.

Tel: 01625 428922 Fax: 01625 433939

Website: www.gradus.com Email: sales@gradus.com

Reference: Esplanade 9000 Primary Barrier Matting

Construction (select as required): Closed or Open (5mm), Single or Double wipers, 12mm or 18mm height

Linking strip material: Mill Finish Aluminium

Wiper colour (select as required): Grey or Plain

Fixing: recessed in matwell – as per manufacturers instructions

Gradus Detailed Specification

Manufacturer: Gradus Accessories, Park Green, Macclesfield, Cheshire, SK11 7LZ.

Tel: 01625 428922 Fax: 01625 433939

Website: www.gradus.com Email: sales@gradus.com

Reference: Esplanade 9000 Primary Barrier Matting

Construction (select as required): Closed or Open (5mm) construction, Single or Double wipers

Linking strip material: Mill Finish Aluminium

Wiper colour (select as required): Grey or Plain

Total height (select as required): 12mm or 18mm

Fire Rating: BSEN 13501-1 Class Cfl-s2

Fixing: recessed in matwell – as per manufacturers instructions

Installation accessories available:

ESP8512ES / ESP8518ES: 12mm / 18mm pvc edging strip

T Bar 12 / T Bar 18: 12mm / 18mm Aluminium divider bar

UMFA12 / UMFA18 / UMFA25: 12mm / 18mm / 25mm aluminium matwell frame

FRB026: 20mm brass matwell frame

Description

Esplanade 9000 is constructed from rubber wipers and aluminium scraper linking strips which are held together with galvanised steel wires. The rubber wipers are available either plain or interwoven with grey polyester fibres. When installed as a true rectangle or a square Esplanade 9000 can be reversed to extend the product's life.

For a complete matting solution Esplanade 9000 can also be used with Boulevard secondary barrier carpet.

Typical applications: Airports, railway stations, supermarkets with heavy wheeled traffic