



GreenUp Track

ST306T P20 930 PSD WB WH BR

GreenUp Track, 20 W, 930 warm white, depends on driver (1-10V, DALI...), Finger-protected

Retail & Hospitality has a clear trend that clusters of choices is one of the most important DNAs that being strongly expected in this specific applications. GreenUp Track product family offers a complete track light solutions with aesthetic and compact product design, comprehensive control availability and specification options. It offers an outstanding color rendering performance and glare control effect, tailored for retail and hospitality applications.

Product data

General Information	
Light source engine type	LED
CE mark	-
Light Technical	
Luminous Flux	1,700 lm
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	85 lm/W
Color rendering index (CRI)	>90
Light source color	930 warm white
Optical cover type	Lens
Operating and Electrical	
Input Voltage	220-240 V
Line Frequency	50 or 60 Hz
Power Consumption	20 W
Power Factor (Fraction)	0.9

Number of products on MCB of 16 A type B	104
Temperature	
Ambient temperature range	-20 to +40 °C
Controls and Dimming	
Dimmable	Yes
Control interface	depends on driver (1-10V, DALI...)
Mechanical and Housing	
Housing Material	Aluminum die cast
Optical cover material	Polycarbonate
Housing Color	White
Optical cover finish	Smoke
Overall length	150 mm
Overall width	95 mm
Overall height	200 mm

GreenUp Track

Dimensions (Height x Width x Depth)	200 x 95 x 150 mm
-------------------------------------	-------------------

Approval and Application

Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK03 [0.3 J]
Protection class IEC	Safety class I

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%

Product Data

Order product name	ST306T P20 930 PSD WB WH BR
--------------------	-----------------------------

Full product name	ST306T P20 930 PSD WB WH BR
Full product code	872016952853699
Order code	911401531122
Material Nr. (12NC)	911401531122
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8720169528536
Numerator - Packs per outer box	12
EAN/UPC - Case	8720169540026

Dimensional drawing

