

SPECIALTY HINGES

DROP LEAF HINGES



BB1279Ball Bearing - Standard Weight

BB1168

Ball Bearing - Heavy Weight

- Drop leaf applied to door will lower the door away from the head 1/8"
- Adjustable to 1/16" drop by repositoning and removing one of the 1/16" spacers
- Non-rising removable pin with button tip and plug
- Handed. Non-reversible
- Also available 1/4" drop

Hinge Size		Gauge of	Hole	Screw Size	
Inches	mm	Metal	Count	Machine	Wood
4-1/2 x 4-1/2	114 x 114	0.134	8	1/2 x 12-24	1-1/4 x 12

Note: Additional sizes and hinges available. Contact Hager Customer Service for information.

UNEQUAL LEAF HINGES



BB1279

Ball Bearing - Standard Weight

- Two ball bearings
- Steel with steel pin
- For use on medium doors requiring medium frequency service

BB1168

Ball Bearing - Heavy Weight

- Four ball bearings
- Steel with steel pin
- For use on heavy doors requiring high frequency service
- For use when door and frame have 4-1/2" and 5" cut-outs
- An equal amount of material is trimmed from the top and bottom leaf
- Two/Four ball bearings
- Non-rising removable pin with button tip and plug
- Handed. Right hand standard.
- Unequal top/bottom available. Contact Hager Customer Service for infomation

Hinge Size		Gauge of	Hole	Screw Size	
Inches	mm	Metal	Count	Machine	Wood
5 x 4-1/2	127 x 114	0.180	8	1/2 x 12-24	1-1/4 x 12

Note: Additional sizes and hinges available. Contact Hager Customer Service for information.

SHORT LEAF HINGES



BB1279

Ball Bearing - Standard Weight

- Two ball bearings
- Steel with steel pin
- For use on medium doors requiring medium frequency service

BB1191

Ball Bearing - Standard Weight

- Two ball bearings
- Brass with stainless steel pin or stainless steel with stainless steel pin
- For use on medium doors requiring medium frequency service

BB1168

Ball Bearing - Heavy Weight

- Four ball bearings
- Steel with steel pin
- For use on heavy weight doors requiring high frequency service

BB1199

Ball Bearing - Heavy Weight

- Four ball bearings
- Brass with stainless steel pin or stainless steel with stainless steel pin
- For use on heavy doors requiring high frequency service
- Short leaf applied to door will move the door 1/8" away from the stop.
 Reverse movement is accomplished by applying the short leaf to the frame.
- Non-rising removable pin with button tip and plug
- Handed. Right hand standard. Reversible to left hand.

Hinge Size		Gauge of	Hole	Screw Size	
Inches	mm	Metal	Count	Machine	Wood
4-1/2 x 4-3/8	114 x 111	0.134	8	1/2 x 12-24	1-1/4 x 12

