

M70-4U-E

Multi-service Video Management Platform



Features :

- 19" standard 4U ATCA industry box
- Easy and flexible configuration with pluggable card module design
- Support HDMI, BNC, DVI and VGA(with converter) and network video input
- Support HDMI, DVI&VGA(with converter) video output
- 80ch@1080P or 320ch@D1 signal encoding (full configured)
- 80ch@4K or 320ch@1080P or 720ch@720P or 1280ch@D1 signal decoding (full configured)
- Support 320ch@1080P H.265 signal decoding(full configured)
- Support 240@D1 nonstandard stream signal decoding(full configured)
- Support max 60 screens splicing
- Support analog/digital video signals input and matrix output
- Support IP camera, NVR, XVR, and PC video signal input
- 6 RJ-45 gigabit network ports for matrix control, preview and online central storage
- Support HTTP/TCP/IP/IPv4/IPv6/UPNP/SMTP/NTP/DNS/DDNS/FTP RTP/RTSP/RTCP/UDP/DHCP/PPPoE, Alarm server
- Support external alarm card and alarm signal management.



Technical Specification

Model

Model	M70-4U-E
-------	----------

System Parameter

Main Processor	Quad-core embedded microprocessor
Operating System	Embedded LINUX
Bus	PCI-E
Slot	12(2 Main Control Board Slot, 10 Video and Audio Function Board)
Mainframe	Power module (redundant power optional), main control board, control board, PCI-E bus rear panel, smart temperature controlled fan
Video Input Card	Max. 10
Video Output Card	Max. 10

Video Input

VIC0201UH-M70 (HDMI)	Interface	2ch HDMI1.4 support HDCP
	Access Capability	2ch@4K, downward compatibility

VEC0404HH-M70 (HDMI)	Interface	4ch HDMI
	Encoding Format	H.264/MPEG4
	Encoding Capability	4CH@1080P, support resolution: 1080P/720P/UXGA/SXGA+/SXGA/XGA/SVGA/VGA
VEC3204FB-M70 (CVBS)	Interface	32ch BNC (1.0Vp-p, 75Ω)
	Signal Format	NTSC/PAL self-adaption
	Encoding Format	H.264/MPEG4
	Encoding Capability	32CH@D1
VEC0404HD-M70 (DVI)	Data Ports	2 RS485 ports
	Interface	4ch DVI-I (HDMI & VGA with convertor)
	Encoding Format	H.264/MPEG4
VEC0404HD-M70 (DVI)	Encoding Capability	4CH@1080P, support resolution: 1080P/720P/UXGA/SXGA+/SXGA/XGA/SVGA/VGA

VEC0804HC-M70 (HDCVI)	Interface	8ch BNC (1.0Vp-p, 75Ω)
	Signal Format	HDCVI (audio/video/control)
	Encoding Format	H.264/MPEG4
	Encoding Capability	8CH@1080P
VEC0804HS-M70 (HD-SDI)	Interface	8ch BNC (1.0Vp-p, 75Ω)
	Signal Format	HD-SDI, 1.485Gbps
	Encoding Format	H.264/MPEG4
	Encoding Capability	8CH@1080P
	Data Ports	2 RS485 ports

Video Output

VDC0605H-M70(HDMI)	Decoding Capability	2CH@32MP(25fps)/8CH@12MP(15fps)/8CH@4K/32CH@1080P/72CH@720P/128CH@D1
	Interface	6ch HDMI
	Resolution	4000*3000@15fps, 3840*2160@30fps, 1920*1080@60fps, 1280*1024@60fps, 1280*720@60fps, 1024*768@60fps
	Split	1/4/6/8/9/16/25/36, free split

Video-Wall

Decoding Card Video-Wall Splicing	Splicing	Support video-wall splicing (max 60 LCD display units)
	Video-Wall	Support Splicing/Zoom/Merge/ Roam/Overlay
	Input Source	HD/SD, Digital/Analog (support mixed input)
	Output Port	HDMI/DVI(HDMI to DVI converter) VGA(HDMI to VGA converter)
	Control Mode	WEB/Local GUI/Video Platform/ Network Keyboard/iPad

Network

Interface	6 RJ-45 ports (10/100/1000M), 2 in mainboard and 4 in control board
Serial Port	4 RS232 ports (4 RJ45), for console and control 1 RS485 port
USB	3 USB2.0, 1 USB3.0

Environmental

Power Supply	100~240V AC, 50/60Hz
Power Consumption	≤600W
Working Environment	-10°C ~+50°C / 10~90%RH / 86~106kpa
Dimension	4U, 482.6 × 437.0 ×177.0mm(19.0 × 17.2 × 7.0 inch), (W*D*H)
Weight	≤25Kg (full configured)

Ordering Information

Type	Part Number	Description
Video Management Platform	DHI-M70-4U-E	4K, H.265 Decoding
	M70-4U-E	4K, H.265 Decoding

Dimensions (mm/inch)

