

FLUSH BOLTS & COORDINATING DEVICES



280X Dust Proof Strike

| | |
|-------------------|--|
| Certification: | Meets ANSI A156.16 for L04021 |
| Face Plate: | 1-7/16" x 2-29/32" x 1/8" depth (37 mm x 74 mm x 3 mm) |
| Barrel Diameter: | 1" (25 mm) |
| Barrel Depth: | 2-3/16" (56 mm) |
| Plunger Diameter: | 3/4" (19 mm) |
| Materials: | Brass |
| Finishes: | US3, US4, US9, US10, US10B, US15, US15A, US19, US26, US26D |
| Fasteners: | Two (2) #8 x 1" FPHWS, two (2) plastic anchors, and spanner wrench |
| Notes: | <ul style="list-style-type: none"> • Packed unassembled with plate, strike, fasteners, and spanner wrench • May be used with carpet or threshold application by omitting face plate • Designed for use with the bottom bolt of a flushbolt set • Spring loaded plunger returns to floor or threshold level anytime flushbolt is retracted, eliminating the need to clean out the bottom strike |



281D Slide Flush Bolt

| | |
|----------------|---|
| Certification: | Meets ANSI A156.16 for L04201 |
| Faceplate: | 3/4" x 6" (19 mm x 153 mm) |
| Bolt Diameter: | 1/2" (13 mm) |
| Bolt Throw: | 1" (25 mm) |
| Bolt Backset: | 7/16" (11 mm) |
| Strike: | 7/8" x 1-3/4" (22 mm x 45 mm) |
| Materials: | Brass, bronze faceplate with steel components |
| Finishes: | US3, US4, US5, US10, US10B, US15, US15A, US19, US26, US26D |
| Fasteners: | Four (4) #6 x 3/4" FPHWS |
| Notes: | Double action spring design provides automatic holding of bolt in projected or retracted position |



282D Manual Flush Bolt

| | |
|----------------------|--|
| Certification: | <ul style="list-style-type: none"> • Fits ANSI A115 door and frame prep • Meets ANSI A156.16 for L14251 |
| Face Plate: | 1" x 6-3/4" (25 mm x 172 mm) |
| Bolt Head: | 1/2" (13 mm) square |
| Bolt Throw: | 3/4" (19 mm) |
| Standard Rod Length: | 12" (305 mm) (center of face to corner of door) |
| Bolt Backset: | 3/4" (19 mm) |
| Mortise Strike: | 15/16" x 2-1/4" (24 mm x 57 mm) |
| Materials: | Brass faceplate with steel components |
| Finishes: | US3, US4, US5, US9, US10, US10B, US15, US15A, US19, US26, US26D |
| Fasteners: | Eight (8) #8 x 3/4" combo screws; eight (8) #8 x 1-1/2" combo screws |
| Notes: | <ul style="list-style-type: none"> • For use on hollow metal/fire-rated doors • Non-handed • Bolt head rods are adjustable • Sold in increments of two • 3 hour fire rating for metal doors up to 4 feet wide by 10 feet tall • 282S strike plate bag and 282P bolt head available • Specify 282R for optional rod length of 18" (457 mm), 24" (610 mm), or 30" (762 mm) (bolt head not included) |

