

TEMPOMATIC 3 electronic tap

Ref. 44200615

Integrated batteries, Ø 15mm stopcock



DESCRIPTION

TEMPOMATIC 3 electronic tap - Ref. 44200615

Deck-mounted electronic basin tap:
Battery-operated with integrated 223 CR-P2 6V Lithium batteries.
Reduced stagnation solenoid valve and electronic unit integrated into the body of the tap.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.

Scale-resistant flow straightener.

Duty flush (~60 seconds every 24 hours after last use).

Active, infrared presence detection, sensor at the end of the spout optimises detection.

Chrome-plated solid brass body.

Cap fixed in place by two concealed screws, with pictogram to easily identify sensor.

PEX flexible Ø 15mm for compression fittings with stopcock and filter.

Fixing reinforced by 2 stainless steel rods.




Anti-blocking security.

Suitable for people with reduced mobility.

10-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC 3 electronic tap - Ref. 44200615

| | |
|--------------|---|
| Supply | 6V battery |
| Connector | M1/2" Ø 15mm |
| Technology | Electronic |
| Drop height | 100mm |
| Spout length | 120mm |
| Flow rate | 3 lpm |
| Norms |   |
| Warranty |  |

ADVANTAGES



Batteries integrated in mixer body



90% water savings



Total hygiene: no manual contact



Duty flush limits bacterial proliferation

