



Uni Line Inground_Wall washer

BBP420 LED 30K 24V B4 L120

Uni Line Inground_Wall washer, 2930 lm, 36 W, 3000 K

Philips UniLine in-ground wall washer is our latest recessed luminaire for outdoor applications. Designed to enhance surroundings in subtle or dramatic ways, this discreet luminaire offers a choice of LED colors and beam angles. So you can light up façades and landscapes with dynamic lighting effects without exposing the body of the device. And because it's compatible with Uni DMX controls and 3rd party standard DMX controls, it's easy to handle too.

Warnings and Safety

- For outdoor use only

Product data

General Information	
Driver included	No
CE mark	CE mark
Flammability mark	-
Light Technical	
Luminous Flux	2,930 lm
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	81.3888888888889 lm/W
Color rendering index (CRI)	>80
Light source color	830 warm white
Optical cover type	Lens

Operating and Electrical	
Input Voltage	24 V
Line Frequency	- Hz
Power Consumption	36 W
Power Factor (Fraction)	1
Connection	-
Cable	2 cables 0.3m with connector 2-pole
Temperature	
Ambient temperature range	-40 to +50 °C
Controls and Dimming	
Dimmable	No

Uni Line Inground_Wall washer

Control interface	-
Mechanical and Housing	
Housing Material	Aluminum
Optical cover material	Acrylate
Housing Color	Aluminum
Approval and Application	
Ingress protection code	IP67 [Dust penetration-protected, watertight]
Mech. impact protection code	IK10 [20 J vandal-resistant]
Protection class IEC	Safety class III
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%

Power consumption tolerance	+/-10%
Product Data	
Order product name	BBP420 LED 30K 24V B4 L120
Full product name	BBP420 LED 30K 24V B4 L120
Full product code	871951452490399
Order code	911401521181
Material Nr. (12NC)	911401521181
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8719514524903
Numerator - Packs per outer box	2
EAN/UPC - Case	8719514525986

Dimensional drawing

