



UniStrip G4

BCP386 30LED 30K 24V A11 L50

UniStrip G4, 485 lm, 7.5 W, Warm white, Safety class III

UniStrip G4 is a surface mounted, exterior-rated LED luminaire that is designed for façade and outdoor architectural lighting applications. One family that fits all your needs, wall washing, grazing and also linear flood lighting. The robust mechanical and unique optical designs make it ideal for illuminating buildings facades, bridges, overpasses and any application that requires a linear lighting solution. Available in white, monochromatic colors, RGB, RGBW and tunable white and DMX control option available with up to 8 pixels (8IDs) to give architects and designers the freedom to explore a wide range of concepts and design with no limitations.

Warnings and Safety

- For outdoor use only

Product data

General Information		Operating and Electrical	
Driver included	No	Input Voltage	24 DC V
Lighting Technology	LED	Line Frequency	- Hz
CE mark	CE mark	Power Consumption	7.5 W
Light Technical		Power Factor (Fraction)	0.9
Luminous Flux	485 lm	Connection	2 Push-in connector 2-pole
Correlated Color Temperature (Nom)	3000 K	Cable	2 cables 0.15m with connectors 2-pole
Luminous Efficacy (rated) (Nom)	65 lm/W	Temperature	
Color rendering index (CRI)	80	Ambient temperature range	-40 to +50 °C
Light source color	Warm white	Controls and Dimming	
Optical cover type	Clear glass	Dimmable	No

UniStrip G4

Control interface	-
-------------------	---

Mechanical and Housing	
Housing Material	Aluminum extruded
Optical cover material	Polymethyl methacrylate
Housing Color	Dark gray
Overall length	500 mm
Overall width	25.4 mm
Overall height	71.6 mm
Dimensions (Height x Width x Depth)	72 x 25 x 500 mm

Approval and Application	
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [1 J]
Protection class IEC	Safety class III

Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%

Product Data	
Order product name	BCP386 30LED 30K 24V A11 L50
Full product name	BCP386 30LED 30K 24V A11 L50
Full product code	871951451396999
Order code	911401780312
Material Nr. (12NC)	911401780312
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8719514513969
Numerator - Packs per outer box	50
EAN/UPC - Case	8719514513969

Dimensional drawing

