


Grooved End Fittings

Small Threaded Reducer

NO. 52



NO. 52



NO. 52F

| Size | No. 52 Small Threaded Reducer | | No. 52F Concentric Reducer with BSPT Female Threaded End | | |
|-------------|----------------------------------|------------------------|--|------------------------|--------------------------------------|
| | Nominal Size Inches mm | E to E Inches mm | Approx. Weight Each Lbs. kg | E to E Inches mm | Approx. Weight Each Lbs. kg |
| 1 1/2 40 | × 1 25 | 2.50 | 0.8 | — | — |
| | | 64 | 0.4 | | |
| | | 2.50 | 0.9 | — | — |
| | | 64 | 0.4 | | |
| 2 50 | × 3/4 20 | 2.50 | 0.9 | — | — |
| | | 64 | 0.4 | | |
| | | 2.50 | 0.7 | — | — |
| | | 64 | 0.3 | | |
| | | 2.50 | 1.2 | — | — |
| | | 64 | 0.5 | | |
| 1 1/2 40 | × 1 1/2 40 | 2.50 | 1.0 | — | — |
| | | 64 | 0.5 | | |
| 2 1/2 65 | × 1 25 | 2.50 | 1.1 | — | — |
| | | 64 | 0.5 | | |
| | | 2.50 (sw) | 1.2 | — | — |
| | | 64 | 0.5 | | |
| | | 2.50 (sw) | 1.3 | — | — |
| | | 64 | 0.6 | | |
| 2 50 | × 2 50 | 3.00 | 1.4 | — | — |
| | | 76 | 0.6 | | |
| 76.1 | × 48.3 | 63.5 | 0.8 | 63.5 | 0.77 |
| | | — | — | | |
| 3 80 | × 3/4 20 | +(sw) | 1.5 | — | — |
| | | — | 0.7 | | |
| | | 2.50 | 1.3 | — | — |
| | | 64 | 0.6 | | |
| | | 2.50 | 1.5 | — | — |
| | | 64 | 0.7 | | |
| 1 1/2 40 | × 1 1/2 40 | 2.50 (sw) | 1.5 | — | — |
| | | 64 | 0.7 | | |
| 2 50 | × 2 50 | 2.50 | 1.5 | — | — |
| | | 64 | 0.7 | | |
| 2 1/2 65 | × 2 1/2 65 | 2.50 | 2.4 | — | — |
| | | 64 | 1.1 | | |
| 88.9 | × 42.4 | 63.5 | 0.9 | 63.5 | 0.82 |
| | | — | — | | |
| | | 48.3 | 0.9 | 63.5 | 0.85 |
| | | — | — | | |
| 4 100 | × 1 25 | 3.00 | 2.3 | — | — |
| | | 76 | 1.0 | | |
| | | 3.00 | 2.7 | — | — |
| | | 76 | 1.2 | | |
| 2 50 | × 2 50 | 3.00 | 2.6 | — | — |
| | | 76 | 1.2 | | |

| Size | No. 52 Small Threaded Reducer | | No. 52F Concentric Reducer with BSPT Female Threaded End | | |
|----------|----------------------------------|------------------------|--|------------------------|--------------------------------------|
| | Nominal Size Inches mm | E to E Inches mm | Approx. Weight Each Lbs. kg | E to E Inches mm | Approx. Weight Each Lbs. kg |
| 4 100 | × 2 1/2 65 | 3.00 | 2.6 | — | — |
| | | 76 | 1.2 | | |
| | | 3.00 | 2.5 | — | — |
| | | 76 | 1.1 | | |
| 108 | × 42.4 | 76.2 | 1.3 | 76.2 | 1.32 |
| | | — | — | | |
| | | 48.3 | 1.3 | 76.2 | 1.39 |
| | | — | — | | |
| 114.3 | × 42.4 | 76.2 | 1.3 | 76.2 | 1.34 |
| | | — | — | | |
| 5 125 | × 4 100 | + | 4.5 | — | — |
| | | — | 2.0 | | |
| 133 | × 60 | — | — | 114.3 | 2.17 |
| 139 | × 60 | — | — | 114.3 | 2.26 |
| 6 150 | × 1 25 | 4.00 | 5.5 | — | — |
| | | 102 | 2.5 | | |
| | | 4.00 | 5.7 | — | — |
| | | 102 | 2.6 | | |
| | | 4.00 | 5.8 | — | — |
| | | 102 | 2.6 | | |
| 3 80 | × 3 80 | 4.00 | 5.8 | — | — |
| | | 102 | 2.6 | | |
| 4 100 | × 4 100 | +(sw) | 6.5 | — | — |
| | | — | 2.9 | | |
| 5 125 | × 5 125 | +(sw) | 2.0 | — | — |
| | | — | 0.9 | | |
| 159 | × 42.4 | 114.3 | 2.2 | 114.3 | 2.45 |
| | | — | — | | |
| | | 48.3 | 2.2 | 114.3 | 2.60 |
| | | — | — | | |
| 165.1 | × 42.4 | 101.6 | 2.4 | 101.6 | 2.95 |
| | | — | — | | |
| 8 200 | × 2 50 | 16.00 | 1.5 | — | — |
| | | 406 | 0.7 | | |
| | | 16.00 | 1.7 | — | — |
| | | 406 | 0.8 | | |

+ Contact Victaulic for details.

Note: All fittings are ductile iron unless otherwise noted with an "sw" or "s"

S= Carbon Steel Direct Roll Groove (OGS)

SW= Carbon Steel Segmentally Welded

IMPORTANT NOTE:

Available with British Standard Pipe Threads, specify "BSP" clearly on order